erve ,933 u63

UNITED STATES DEPARTMENT OF AGRICULTURE Rural Electrification Administration Washington 25, D. C.

TECHNICAL STANDARDS COMMITTEES Month of March 1950

The following is a summary of the changes in the "List of Materials Acceptable For Use on REA-Financed Systems" resulting from decisions of the Technical Standards Committees during the month of March 1950:

1. Page Da-1 - Insulators, pin type

Change Lapp numbers in first three columns to read as follows:

KV Class:	Delta 5	5tar 7.2/12.5	Delta 15
(l-piece) (multi-part)	6188	6184	7385

2. Page D af-2 - Cutout, fuse, single-shot, open - Distribution

Add Joslyn numbers J9234-6 and J9234-5 to replace numbers J9234-4 and J9234-3, respectively.

3. Page D ap - Clamps, hot line

Change Dave Nelson Company numbers to read as follows:

Page ap-6

ACSR Gauge Diam., inches, bare Diam., inches plus rods	4/0	3/0	2/0 - 6/1	1/0-6/1	2	4
	0.563	0.502	0.447	0.398	0.325	0.257
	0.939	0.836	0.745	0.744	0.595	0.555
Manufacturer			Catalog	Number:		

Manufacturer
Nelson AA*
- - - 2020-4 2020-4
AC*
- - - 2020-2 2020-2

AA* - Indicates connection from Al over armor rods to Al.

AC* - Indicates connection from Al over armor rods to Cu or Cwld.

2-Technical Standards Committees Materials List Changes - Month of March 1950

Pag	e a	p-7

Steel	4	6		8			
Amerductor Gauge Diam.,inches	0.310	6	8 0.196	8X 0.216	9X 0.192	10 0.220	12 0.175
Manufacturer			Cat	alog Num	ber:		
Nelson AA AC	2020 - 4 2020 - 2	2020 - 4 2020 - 2	1010-4	1010-4		1010-4	1010-4

Note: These clamps are to be used for replacement purposes only.

4. Page D as - Clevis, service, swinging, insulated

Add Seyler numbers 1938-M and 1948-M to replace numbers 1938 and 1948, respectively.

5. Page D ax - Cutout and arrester, combination

Add Joslyn numbers J9237-6 and J9237-5 to replace numbers 9237-4 and 9237-3, respectively. Add crossarm mounting number J9201D to replace number J201D.

6. Page D by - Armor Rods

Add the following:

Manufacturer	Type	Description
Indiana Steel & Wire Co. Reynolds	Preformed Preformed	Aluminum Aluminum

7. Page D ci - Clevis, thimble, side-opening

Add Line Material number SA475X1.

8. Page D cy - Sleeve, splicing, compression type

Add Burndy numbers as follows:

ACSR Gauge Diam.(inches)		2/0-6/1 0.447	1/0-6/1 0.398	2-7/1 0.325	2-6/1 0.316	4-7/1 0.257	4 - 6/1 0.250
Burndy	YDS27R	YDS26R	YDS25R	YDS021R	YDS2R	YDS041R	YDS4R

- 3-Technical Standards Committees
 Materials List Changes Month of March 1950
- 9. Page D eb Brackets, pole top for post type insulators

Add Lapp number 10765.

Add Ohio Brass number 84324.

10. Page D ek - Locknuts

Add Kortick numbers K1066, K1067, and K1068 under $1/2^n$, $5/8^n$, and $3/4^n$, respectively.

11. Page D gb - Meter Sockets

Add the following:

Manufacturer	Type	Catalog Number
General Electric		378 x 7
Westinghouse	STU	1537445, 1537450

12. Page D xx-1 - Service Control Equipment

Add Heinemann numbers as follows:

Manufacturer	Description	Rating of fuse or breaker		Maximum Recommended Transformer Size
Heinemann	Enclosure and breakers	1-35 amp. 2-70 amp. 2-100 amp.	MH801-35 H1002-70 H1002-100	1½ kva 10 kva 15 kva
	Combination socket) enclosure & breakers)	2-70 amp. 2-100 amp.	H1202-70 H1202-100	10 kva 15 kva
	Breaker only	1-70 amp. 1-100 amp.	1163C-70 1163C-100	
	Enclosure only		H1000	

Add Murray numbers 1961-T-35, 1962-T-35, and 1962-T-50 to replace numbers 1961-35, 1962-35, and 1962-50, respectively.

13. Page T by - Armor Rods

Add the following:

Manufacturer	Type	Description	
Indiana Steel & Wire Co. Reynolds	Preformed Preformed	Aluminum Aluminum	

- 4-Technical Standards Committees
 Materials List Changes Month of March 1950
- 14. Page T cy Sleeves, splicing, compression type

 Add Burndy numbers as follows:

ACSR
Gauge 3/0 2/0-6/1 1/0-6/1
Diam.(inches) 0.502 0.447 0.398

Burndy YDS27R YDS26R YDS25R

15. Page T eb - Brackets, pole top for post type insulators
Add Lapp number 10765.

Add Ohio Brass number 84324.

16. Page T ed - Support, overhead ground wire with link and load plate
Add Locke numbers as follows:

Pole top diam. inches 6 to 8 8 to 10 10 to 12

Manufacturer Catalog Number

Locke 5431 5432 5433

17. Page T ek - Locknuts

Add Kortick numbers Kl066, Kl067, and Kl068 under $1/2^n$, $5/8^n$, and $3/4^n$, respectively.

- 18. Remove all catalog numbers for the International Derrick and Equipment Company from pages "D c," "D d," "D h," "D i," "D j," "D n," "D o," "D u," "D aa to ad," "D ai," "D bb," "D bj," "D bk," "D bm," "T c," "T d," "T j," "T o," "T u," "T ai," "T bj," "T bk," and "T dy."
- 19. Remove all catalog numbers for Sheldon Service Corporation from pages "D p-lb" and "T p-lb."

